

Product Safety Data Sheet

XEROX

Product: 8840-D

PSDS No.: 0685

ISSUE DATE: 11/15/91

REV. DATE: 6/19/95

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Manufacturer's Address

Fuji Xerox Co. Ltd
Iwatsuki-Shi
Saitama-Ken 339, Japan

Product Designation

8840-D
Stacker Accessory

Emergency No. EH&S Inquiries

(585) 422-2177 (800) 828-6571

Product Identifier

Printer 9P6
Stacker 9R0

Section II - Electrical Information

Line Voltage

(Volts)
115

Line Current

(Amps)
11.4

Freq.

(Hertz)
60

Branch Cir. Protection

(Amps)
15 A

Line Cord/Plug Specification

Cord: Type SJT, 14 AWG, 2-wire plus ground
Plug: NEMA 5-15

Power Consumption (Watt)*

Running: 1344
Standby: 316

Agency Approval

UL File Number: E51242

CSA LR Number: 51205

Section III - Supplies

Black Toner Cartridge
Xerox Drum

Xerox Part No.

6R349
1R117

Material Safety Data Sheet

A-0082
Article** (C23)

Section IV - Environmental Information

Product Size

(Centimeters/Inches)

Printer	Stacker
D: 95 / 37	D: 87 / 34
W: 60 / 24	W: 75 / 30
H: 101 / 39	H: 87 / 34

Heat Emission*

(BTU/HR)

Running: 4602
Standby: 2410

Environmental Limitations

	Min	Max
Relative Humidity (%)	15	85
Ambient Temp. (oC)	10	35

Floor Space Requirements

(Meters/Feet)

2 x 2 / 8 x 8 (without Stacker Accessory)
3 x 2 / 10 x 8 (with Stacker Accessory)

Weight

(K Grams/Lbs.)
250 / 551

* Based on a five minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2))

Section V - Emission/Exposure Information***Light Source**

LED Display (not visible)

Electromagnetic Emissions

US FCC: Class A

Canada DOC: Class A

Audible Noise

Run 51.6 db (A)

Standby 38.1 db(A)

Impulse 66.0 db(A)

TLV

85 db(A)

Ozone

Concentration Based on Simulation Model:

Daily Copy Volume 164

Room Size 18.4 cubic meters

1/2 Air Room Change per Hour

130.15 ug/min

0.005 ppm (TWA)

0.008 ppm (STEL)

TLV

0.1 ppm

Total Dust<0.1 mg/m³**TLV**10 mg/m³**Organics**

<10 ppb

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.