Xerox[®] EX 280 Print Server Powered by Fiery[®] v3.0

Build a more profitable future with the Xerox[®] Versant[®] 280 Press and an easy-to-use, powerful digital front end that delivers outstanding quality and best-in-class performance.

MORE HIGH-VALUE JOBS, FASTER

Meet critical customer turnaround times and increase production capacity with the EX 280 Print Server, which processes jobs over 30% faster compared to the EX-i 280 Print Server.

GET OUTSTANDING COLOR EVERY TIME

Fiery Edge technology gets the most precise and stunning results from Fiery Driven printers. It achieves the best- possible gamut for both spot and process color reproduction.

With Fiery Spot-On and Fiery TrueBrand, you can ensure accurate spot colors on all job types — even Microsoft Office documents.

Fiery Ultra Smooth Gradients combines 10-bit architecture and special processing to deliver stunning, smooth gradients that will delight your customers by printing with the true appearance designers intended.

BOOST PROFITS WITH PERSONALIZATION

The EX 280 Print Server supports all variable data printing (VDP) formats. Or use Fiery FreeForm Create, an included application that allows you to quickly and simply create personalized jobs for print production. Add variable elements such as text, images, or barcodes with just a few clicks.

BUILT-IN PRINT INTELLIGENCE

Fiery JobExpert analyzes files and dynamically chooses the optimal print settings. So anyone can print jobs correctly — no expert knowledge required.

POWER TO THE OPERATOR

Gain complete control of how and when jobs print. Job Groups makes it easy to print a group of jobs in a specific order or group jobs together for multi-job makeready using Fiery Impose. With Fiery Print Scheduler, it's a breeze to schedule jobs to best align with daily production demands. Fiery Preflight provides basic preflight checks to help spot file problems before printing.

Easy Vitals for the Xerox® Versant 280 Press constantly compares the current press state with the recommended state to ensure the press is operating within the correct tolerances.

The included Fiery Impose simplifies layout work with intuitive, visual document imposition. You can even integrate with offline finishers to automate processes from prepress to finishing, reducing job setup time by up to 70%.



Powered by



Xerox

DIMENSIONS/WEIGHT

Weight: 36.5 lb (16.5 kg

Xerox® FreeFlow® Vision Software,

INTEGRATION

Fiery API

Fiery JDF v1.8

UK CA Mark (UK)

Spectrophotometer

Fiery NX Station GL

Suite (ACQS) software.

FIERY HARDWARE AND

Fiery Graphic Arts Pro Package²

ES-3000 Spectrophotometer

Fiery disk drive security kit

Adobe® Acrobat® Pro Kit

Fiery Compose²

Fiery Hub Kit Fiery JobMaster²

Fiery Manage³

Fiery ColorGuard²

Fiery NX Station GL

Fiery Color Profiler Suite4 with Fiery

Additional Fiery Impose licenses

Fiery ES-6000 spectrophotometer

¹ Updated with enhancements and service

³ With proper configuration by the end customer or

xerox

releases on an ongoing basis

² Free 30-day trial available

4 Free trial in demo mode

service provider

Fiery High Security Kit (includes trusted platform

module (TPM), enables OS drive encryption)

SOFTWARE OPTIONS

Fiery Compose

Xerox® FreeFlow® Core

Xerox Standard Accounting

Print Server: 20.75" (527.05 mm) H x 9.25"

(234.95 mm) W x 18.25" (463.55 mm) D

MIS and Web-to-Print integration ready

Prepress workflow integration (Heidelberg® Prinect,

Kodak® PRINERGY, Agfa® Apogee, SCREEN EQUIOS)

Safety: CB Scheme – 62368-1, 2nd/3rd Edition, CU-Mark

REGULATORY AGENCY APPROVALS

(US and Canada), T-Mark (EU), UK CA Mark (UK)

XEROX PERFORMANCE PACKAGE

Fiery Color Profiler Suite 4 with Fiery ES-3000

for All Stocks Rated Speed (ASRS) with ILS

(RECOMMENDED CONFIGURATION)

Xerox Interface Decurler Module (IDM/ILS) hardware

Includes Fiery Spot Pro, Fiery ImageViewer, Fiery

Preflight Pro, Fiery Postflight, Fiery Control Bar

functionality, and Xerox Automated Color Quality

FMI/FMC: FCC and ICES-003 (US and Canada), CE

Mark (EU), RCM Mark (Australia and New Zealand),

HARDWARE/PLATFORM

- Fiery FS600 Pro software
- Intel[®] Core i5-8500 Processor
- SSD boot drive for OS & Fiery software + 1 TB HDD
- 8 GB RAM
- Fiery QuickTouch software
- USB 3.0 ports (2 rear, 3 on Fiery QuickTouch panel)
- Microsoft® Windows® 10 IoT Enterprise 2021 LTSC
- Fiery Installer Builder
- USB media server •

FIERY COLOR AND

IMAGING TECHNOLOGY

- Fiery Edge color profiles
- Fiery Edge spot color processing
- Fiery TrueBrand
- Fiery Ultra Smooth Gradients
- 1200 x 1200 dpi, 10-bit rendering resolution
- Ultra High Definition Resolution
- Fiery Smart Estimator
- RGB and CMYK rendering intent control
- Object Oriented Halftones
- PANTONE® Color Enabled
- Fiery Spot-On
- Composite overprint
- Calibration
 - Fiery Calibrator ColorCal (standard, off the glass)
 - _ Fiery ES-3000 spectrophotometer (optional)
 - Inline Spectrophotometer (ILS) (optional)
 - Job-based calibration
 - Calibration Guard
- Image smoothing
- Fiery Image Enhance Visual Editor
- Text and graphics enhancement: text/graphics quality, color text and graphics enhancement, trailing edge compensation, black text and graphics anti-aliasing, text/graphics sharpness
- Supports Xerox® Adaptive CMYK+ Kit

PERFORMANCE

- SmartRIP
- Spool-RIP-Print
- Scan-RIP-Print
- Strict ordered printing

ADOBE INTERPRETER SUPPORT

- Adobe[®] PDF Print Engine[®] version 6.0¹
- CPSI version 3020

VARIABLE DATA PRINTING

- Fiery FreeForm Create
- Supported file formats:
- Fiery FreeForm Plus
- PPML v3.0 _
- PDF/VT-1 and 2
- Creo VPS
- VI Compose, Xerox® VIPP® Language,
- Xerox Specialty Imaging/FreeFlow® VI Suite VDP record and set level finishing, define record length, VDP multi-up booklet, VDP Imposition

FILE FORMAT SUPPORT

- Adobe® PostScript® Levels 1, 2, 3; Adobe PDF; PDF/X-1a, 3, and 4; EPS; JPEG; TIFF
- Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, pub (via Hot Folders)

For more information on the Xerox® EX 280 Print Server Powered by Fiery® for the Xerox® Versant® 280 Press, please contact your Xerox representative,

© 2024 Xerox Corporation, All rights reserved, Xerox®, FreeFlow®, Versant®, and VIPP® are trademarks of

Xerox Corporation in the United States and/or other countries. 05/24 TSK-5707 BR34607 V28SS-02UD

call 1-800-ASK-XEROX, or visit us online at www.xerox.com.

PRODUCTIVITY AND WORKFLOW

- Easy Vitals for Xerox[®] Versant[®] 280 Press
- Fiery Command WorkStation
- Fiery JobExpert
- Accessible from Xerox® FreeFlow® Core
- Includes exclusive settings for the Xerox® Versant® 280 Press
- Fiery Impose
- Job Groups
- Print Group
- PDF Group
- Fiery Print Scheduler
- Print Time Estimation
- **Fierv** Preflight
- Rush Print, Suspend on Mismatch, Print Next/Process Next, Sample Print, Proof Print, Force Print
- Fiery Drivers for Windows and Mac
- Fiery WebTools
- Fiery Hot Folders/Virtual Printers
- Fiery server presets
- Booklet Maker
- Fiery Remote Scan
- Set Page Device Mapping
- Pad printing
- Visual image shift
- Auto trapping
- Paper Catalog
- Fiery VUE
- Fiery Go (Android and iOS)
- Direct mobile printing Mixed Subset Finishing
- Slip sheet, job cover page, and offset by sheets, copies, or sets
- Fiery Custom Crease
- Copy numbering
- GUI-enabled

NETWORKING/CONNECTIVITY

- TCP/IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication
- Login with SSO (single sign-on)
- Native support for Universal Print by Microsoft®
- Compliant with Mopria® industry standard

SECURITY FEATURES

- Secure Erase (NIST 800-88 compliant), Security profiles, Security Audit Log
- Secure Boot

IPsec encryption

POWER

7 Amp @ 100 V

OS drive encryption (requires Fiery High Security Kit)

image to meet security compliance requirements

Port blocking, IP filtering, 802.1X authentication,

TLS 1.3 support for encrypted communications:

Secure printing, PostScript security, USB security

Auto-switching: 100-240 VAC, 7-3.5 Amps, 50/60 Hz

Typical: 100 W, 1 Amp @ 100 V. Maximum: 350 W,

Fiery WebTools, IPP, Direct Mobile Printing

Enhanced certificate management

Digitally signed software updates

Fiery self-signed certificates are

recreated automatically

FIPS 140-2 compliant data encryption. Common Criteria compliant ³ Option to use a customer hardened Windows OS